

Claims:

1. (Currently amended) A method for applying walkway pads to roofing membranes, the method comprising:
affixing a ~~solids~~ an adhesive tape to one flat surface of a walkway pad, where the tape carries a protective layer of release paper, and where said step of affixing occurs at the location where the pad is manufactured;
removing said release paper from said tape immediately prior to use;
subsequently placing the exposed surface of said tape directly onto the upper surface of the roofing membrane; and,
applying force directly to said walkway pad ~~to enhance the bond between said pad and the membrane created by said tape.~~
2. (Previously presented) The method of claim 1, where said walkway pad comprises asphaltic materials, concrete or rubber-based materials.
3. (Currently amended) The method of claim 1, wherein said ~~solids~~ tape comprises EPDM rubber, butyl rubber or blends thereof.
4. (Currently amended) The method of claim 1, wherein said walkway pads comprise rubber-based materials and said ~~solids~~ tape comprises a blend of EPDM and butyl rubbers.
5. (Cancelled)
6. (Previously presented) The method of claim 1, further including the additional step of preparing the area of the roofing membrane to which said walkway pad will be applied ~~prior to said step of removing.~~
7. (Previously presented) The method of claim 6, wherein said step of preparing includes the step of priming the area of the roofing membrane to which said walkway pad will be applied prior to said step of removing.

8. (Currently amended) A method for applying a walkway pad to a roofing membrane, said method comprising:

providing a walkway pad to a rooftop, where the walkway pad includes a ~~solids~~ an adhesive tape applied to a substantially planar surface of the walkway pad; and

applying the walkway pad to a roofing membrane, which is located on the rooftop, by placing an exposed surface of the ~~solids~~ tape directly onto the upper surface of the roofing membrane.

9. (Cancelled)

10. (Previously presented) The method of claim 8, where said walkway pad comprises asphaltic materials, concrete or rubber-based materials.

11. (Currently amended) The method of claim 8, wherein said ~~solids~~ tape comprises EPDM rubber, butyl rubber or blends thereof.

12. (Currently amended) The method of claim 8, wherein said walkway pads comprise rubber-based materials and said ~~solids~~ tape comprises a blend of EPDM and butyl rubbers.

13. (Previously presented) The method of claim 8, further including the additional step of

preparing the area of the roofing membrane to which said walkway pad will be applied prior to ^{was} said step of removing

14. (Currently amended) The method of claim 8, where the ~~solids~~ tape is applied to a flat surface of the walkway pad at the same location where the walkway pad is manufactured.

15. (Currently amended) The method of claim 14, where the ~~solids~~ tape is applied to a flat surface of the walkway pad without priming the flat surface of the walkway pad.

16. (Currently amended) A method for providing walkway pads to service personnel who will apply the pads to a roofing membrane, said method comprising:

preparing a self-adhering walkway pad by affixing ~~a solids~~ an adhesive tape to a flat surface of a walkway pad, where said ~~solids~~ tape carries a protective layer of release paper;

bundling a plurality of self-adhering walkway pads for delivery; and,

delivering the plurality of self-adhering walkway pads to service personnel for application of the walkway pads to a roofing membrane.

17. (Previously presented) The method of claim 16, where said walkway pad comprises asphaltic materials, concrete or rubber-based materials.

18. (Currently amended) The method of claim 16, wherein said ~~solids~~ tape comprises EPDM rubber, butyl rubber or blends thereof.

19. (Currently amended) The method of claim 16, wherein said walkway pads comprise rubber-based materials and said ~~solids~~ tape comprises a blend of EPDM and butyl rubbers.

20. (Cancelled)

21. (Currently amended) The method of claim 16, where the ~~solids~~ tape is applied to a flat surface of the walkway pad at the same location where the walkway pad is manufacture.

22. (Currently amended) The method of claim 16, where the ~~solids~~ tape is applied to a flat surface of the walkway pad without priming the flat surface of the walkway pad.

23. (Previously presented) The method of claim 16, where the tape is a 100% solids tape.

24. (Previously presented) The method of claim 8, where the tape carries a protective layer of release paper; and further comprising the step of removing the release paper from the tape.

25. (Cancelled)

26. (Cancelled)

27. (Currently amended) A method of making a walkway pad, said method comprising the steps of:

constructing a walkway pad within a factory;

applying a ~~solids~~ an adhesive tape to a substantially planar surface of the walkway pad; and

applying a release paper directly to said ~~solids~~ tape, where said steps of applying a ~~solids~~ tape and applying a release paper occur while the walkway pad remains within the same factory that the walkway pad was constructed.

102
28. (Previously presented) The method of claim 8, where the walkway pad is about 30 inches square.

102
29. (Previously presented) The method of claim 8, where the walkway pad has a thickness of about 0.25 to about 0.5 inches.

102
30. (Previously presented) The method of claim 8, where the walkway pad has a thickness of about 0.30 inches.

103 Tajma
31. (Previously presented) The method of claim 8, where the upper surface of the walkway pad is textured.

103 Tajma
32. (Previously presented) The method of claim 1, where the walkway pad is rubber-based.

ant 107
E (Tiger)
33. (Previously presented) The method of claim 1, where the roofing membrane is rubber-based.
